

Sievers* Soleil Rapid Bioburden Analyzer

Get bioburden results in less than 45 minutes
with proven correlation to plate counts



The Sievers Soleil

The Sievers Soleil Rapid Bioburden Analyzer is a Rapid Microbial Method (RMM) that monitors bioburden at ultrapure levels in less than 45 minutes - finally providing the ability to detect microorganisms in near real-time. With data correlating to plate counts, you can make data-driven decisions and take quick action to control contamination throughout the manufacturing process.

Time to results in less than 45 minutes

- Enables data-driven decisions and quick action for controlling contamination
- Unique reagents and viability stain combinations detect viable cell counts from Gram-negative bacteria, Gram-positive bacteria, yeast, and mold
- High-throughput flow cytometer distinguishes between viable cells and abiotic particles using proprietary fluorescent stains to ensure accuracy and sensitivity
- Measures not only water but also complex samples including drug substances, culture media, plastics, and more

Better contamination control + increased manufacturing agility = cost savings

With the Soleil RMM, productivity is increased without jeopardizing patient safety and while reducing risk to release materials or products. Rapid results means faster decision making, which leads to cost savings at many points during manufacturing:

- Pharmaceutical manufacturing water – critical control points
- Cleaning validation / hygiene monitoring
- Process water
- Raw materials
- At-line monitoring of drug substances and intermediate products
- Environmental monitoring of process areas

Straightforward sample preparation

The Soleil system can be used in a laboratory or at-line and preparing samples is quick and easy. First, the sample is heated to 37° C for a brief period in the onboard incubator. Next, add Soleil Reagent A followed by Soleil Reagent B. After a 15 minute incubation period, simply add Soleil Reagent C. The Sievers Soleil will analyze the sample with results in 15 minutes or less, depending on the sample volume.

Microbial monitoring with ease

Microbial monitoring is faster and easier with the Soleil's simple set up, software, and consumables. Here's what you can expect day to day:

- Software that walks you through each step for daily start up
- Less time (or no time!) spent working in a biological safety cabinet streaking plate after plate
- No need to purchase filters, agar plates, or multiple pipette tips - with the Soleil you just need the recommended pipette tips and bottles
- Simplified, high throughput testing for sample volumes 20-100 mL

Specifications

Operating Specifications

Range	<10 biotics/100 mL - 10,000 biotics/100 mL
Sample Type	Discrete grab sample
Display Readout	Biotics/100 mL
Calibration	Typically stable for 12 months
Analysis Time	< 45 minute Total Time to Result (TTR)
Sample Temperature ¹	35-39 °C (95-102.2 °F)
Ambient Temperature	17-30 °C (63-86 °F)
Sample Pressure	N/A
Instrument Sample Flow Rate	8 mL/min

Analyzer Specifications

Outputs	USB port, Ethernet TCP/IP
Display	14" laptop touchscreen (1920x1080)
Power	100-240 V~, 50-60 Hz, 165 VA
Fuses	Qty 2; T 5A 250 VAC Replace with same type and size fuse Size 5x20 mm appliance inlet
Laser (Class 1)	Wavelength: 488 nm Max Power: 135 mW
Dimensions	Width: 48.3 cm (19 in) Depth: 43.2 cm (17 in) Height: (without laptop): 43.2 cm (17 in)
Weight	18.1 kg (40 lb)
Enclosure Rating	IP30
Safety Certifications	ETL, CE, UKCA, FCC, CSA 22.2

Environment

Maximum Relative Humidity	0-85%, non-condensing
Maximum Altitude	3,000 m (9,800 ft)
Pollution Degree	2

¹ Driven by onboard incubation

This information herein may be subject to change without notice and is provided for general guidance only. The dimensions and performance of systems, products and services may vary. Pictures are for example purposes and not to scale. All legal obligations are exclusively as set out in contractual documents. Nothing contained herein constitutes a representation, warranty or undertaking.



6060 Spine Road
Boulder, CO 80301-3687 USA
T +1 800 255 6964
T +1 303 444 2009
F +1 303 527 1797

watertechnologies.com/sievers

